Date:

6/23/2006 7:38AM

User:

Kim Johnston

PROCESS SHEET

Job No.

: CU-DAR001 Dart Helicopters Services

: 10523 Estimate No.

P.O. No. First Issue Prsht Rev. : 27671

25980

SO NO. NA

Type : MACHINED PARTS 6/23/2006

Drawing Name Part No. Drawing No.

Drawing Rev. Project No. Material **Due Date**

SADDLE, OUTBOARD, RH, 206

D26652 D2665 REV. B

В

N/A NA

7/15/2006

QTY:

12

Prev. Run Written by:

This Issue

Checked & Approved by:

Comment:

Est:

Removed P/O for Powder Coat - in house process

EC

Job Number:



Seq. No. 1.0

Machine or Operation



1.0000 Each(s)/Unit

7075-T7351 2X6.25X7.875 Cut Size 2.0" x 6.25" x 7.88" Total:

B24891

Grain Along Long 7.88 Length

2.0

HAAS1

HAAS CNC VERTICAL MACHINING #1



Comment:

HAAS CNC VERTICAL MACHINING #1

1- Program batch number

- 2- Machine Step # 1 of Folio and visually inspect as per attached Dimension Sheet
- 3- Machine Step # 2 of Folio and visually inspect as per attached Dimension Sheet
- 4- Machine Step # 3 of Folio and visually inspect as per attached Dimension Sheet

5- Deburr

06/06/26

3.0

MILLING CONV

CONVENTIONAL MILLING MACHINE



Comment:

CONVENTIONAL MILLING MACHINE

Machine Keyway and inspect per attached dimension sheet

06107

4.0

QC2

INSPECT PARTS AS THEY COME OFF MACHINE



Comment:

INSPECT PARTS AS THEY COME OFF MACHINE

06/06/26

5.0



6.0

SECOND CHECK

06107126

HAND FINISHING1

HAND FINISHING RESOURCE #1



HAND FINISHING RESOURCE #1 Acid etch and Alodine as per QSI 005 4.1

Dart Aerospace Ltd

H:\forms\Quality Assurance\approved forms\NCRWO revC

W/O:		-	V	ORK ORDER	CHANGES				
DATE	STEP	PRO	CEDURE CH	IANGE		Ву	Date Qty	Approval Mfg / Design Mgr	Approval QC Inspector
ſ									
									2
NCR:		٠ ني	VORK OR	DER NON-COI	NFORMANC	E (NCR)			1
DATE	STEP	Description of NC Section A	Initial Design Mgr	Corrective Act Action Design	scription	Sign & Date	Verification Section C	Approval Design Mgr	Approval QC Inspector
					<u>.</u>		<i>.</i> .		
		;		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		0.2			
						4	7.6	•	
									<u>.</u>
									2 : 1
		PAR #:al all entries	Fault Categ	ory:		es (No) D A: N/C Clos	QA:	_ Date: <u>Ò</u> ∠ Date:	0107/28

Job Number:



Seq. No.	Mac	hine or Operation	Description		
7.0	POWDER COAT	ING	POWDER COATING		
	Comment:	POWDER COATING	40.74	0 0/ -> 0	
		Powder Coat White Gloss (Ref:	4.3.5.1) as per QSI 005 4.3	CHEMICAL CONVERSION	<i>((13</i>)
8.0	QC3		INSPECT POWDER COAT/	CHEMICAL CONVERSION	
				182601/27	(2)
	Comment:	INSPECT POWDER COAT			
9.0	PACKAGING 1		PACKAGING RESOURCE #	¥ 1	
	Comment:	PACKAGING RESOURCE #1 Identify and Stock Location: \$T483		Al 06/07	10 D
10.0	DC		DOCUMENT CONTROL		
	Comment:	DOCUMENT CONTROL Inspection Level 21		\$ 06/07/2	
Job Completion				\$ 06/07/2 \$ 06.07.2	28

Dart Aerospace Ltd

W/O:				W	ORK OR	DER CH	ANGES						,
DATE	STEP	PRO	CEDUR	E CH	ANGE			Ву		Date	Qty	Approval Mfg / Design Mgr	Approva QC Inspector
								-					
									:				
					***					Ň			
			•							•			•
	·												
		:										· · · · · · · · · · · · · · · · · · ·	
NCR:			WORK	ORI	DER NON	I-CONF	ORMANO	CE (N	CR)		• .	· · · · · · · · · · · · · · · · · · ·	
		Description of NC			Correct	ve Action	Section B	-	; i	Verific	ation*	Approval	Approval
DATE	STEP	Section A	Initia Design		Acti	on Descri Design Mgr	ption	Sig Da	n &∃ ite	Secti		Design Mgr	QC Inspecto
rg-													
							·			,	. 140	· .	
													
*		·									·		
•					* •			· a					
				1								•	
er e					•								
					•						·		
		· · ·		-								•	
D - 4 N		\$		1									
		PAR #:	Fault Ca	atego		····				QA:		Date:	
NOTE: D	ate & initia	al all entries		1	•	•		A: N/C	Clos	sed:		Date:	<u> </u>

H:\forms\Quality Assurance\approved forms\NCRWO revC

DART AEROSPACE LTD	Work Order:	27671
Description: 206 Saddle, Outboard, Right side	Part Number:	D2665-2
Inspection Dwg: D2665 Rev. B		Page 1 of 1

Inspect dimensions highlighted on inspection sheet drawing D2665 Rev. B and record below:

				Re					
Dim	Min	Max	Go/No Go Gauge	1	2	3	4	Ву	Date
Α	0.100	0.140		-120	. 121	125	.127	1	
В	0.100	0.140		-117	122	.126	.128		
С	0.100	0.140		. 119	172	126	-12la		
D	0.210	0.230		-216	- 220	220	- 22[
Е	1.245	1.255		1,250	1.250	1.250	1.250		
F	1.245	1.255		1-250	1,250	1.250	1,249		
G	5.990	6.010		6.000	5.998	5.999	5.998		
Н	0.510	0.515		0.5/5	0.515	0.515	0.575		
ı	1.674	1.684		1.678	1.678	1.679	1-644		
J	2.495	2.505		2.491	2.500	2,499	2.499		
K	0.257	0.262	DT8683	1	1,	-			
L	0.312	0.317	DT8686						
M	0.235	0.240		0.235	6.237	0.237	£23.8		
N	0.100	0.140		-/09	./21	121	. 123		
0	0.540	0.560		.549	.548	.547	. 545		
P	0.490	0.510		-500	. 203	.505	.500		
Q	3.609	3.619		3.614	3614	3.6/3	3.614		
R	2.470	2.510		2.500	2.500	2.500	2.500		
S	0.240	0.270		-249	-251	1252	.252		
T	0.100	0.180	3	1.145	.145	.145	-145		
U	0.313	0.318	DT8686			/			
V	1.125	1.145		1./33	1.134	1./35	1.137		
W	1.565	1.585		1.568	1.574	1.573	1.576		
Χ				110 60					
Υ									
Z			,						
AA			1						
AB								1	-
AC									
AD		*							
AE				T		1			
AF					1				
AG									
AH		.,,				<u> </u>			
	Acc	ept/Reje	ct						

	• •			
	Measured by:	J.L.	/ Cp.	Audited by 5.6
1	Date:	06/06/25	1 066774	Date: 06/07/26
			1101	

Rev	Date	Change	Revised by	Approved
Α		New Issue	RF	
В	99.04.19	Incorporated DSI 9095, DSI 9102 & DSI 9122 Rev. A	RF	
C	99.11.10	Added Dim. R-T	RF	<u> </u>
D	02.12.12	Reformat; Added Dim. U-W & DT8683, DT8686	KJ/RF	+

DART AEROSPACE LTD	Work Order:	27671
Description: 206 Saddle, Outboard, Right side	Part Number:	D2665-2
Inspection Dwg: D2665 Rev. B		Page 1 of 1

Inspect dimensions highlighted on inspection sheet drawing D2665 Rev. B and record below:

Dim Min Max Go/No Go Gauge 1 A 0.100 0.140 ./2/3 B 0.100 0.140 ./2/3 C 0.100 0.140 ./2/3 D 0.210 0.230 ./2/3 E 1.245 1.255 ./2/3 F 1.245 1.255 ./2/3 G 5.990 6.010 5.996 H 0.510 0.515 ./2/3 I 1.674 1.684 ./2/3 J 2.495 2.505 ./2/3 K 0.257 0.262 DT8683 ./2/3 L 0.312 0.317 DT8686 ./2/3 N 0.100 0.140 ./23 O 0.540 0.560 ./43 P 0.490 0.510 Q 3.609 3.619	Recorded Actual Dimensions				
B 0.100 0.140	2	3	4	Ву	Date
C 0.100 0.140 D 0.210 0.230 E 1.245 1.255 F 1.245 1.255 G 5.990 6.010 H 0.510 0.515 I 1.674 1.684 J 2.495 2.505 K 0.257 0.262 DT8683 L 0.312 0.317 DT8686 M 0.235 0.240 N 0.100 0.140 O 0.540 0.560 P 0.490 0.510 Q 3.609 3.619 R 2.470 2.510 S 0.240 0.270 T 0.100 0.180 U 0.313 0.318 DT8686 X Y 1.125 1.145 W 1.565 1.585 X Y Z AA AB AB AC AD AE AF	. 122	122	120		
C 0.100 0.140 D 0.210 0.230 E 1.245 1.255 F 1.245 1.255 G 5.990 6.010 H 0.510 0.515 I 1.674 1.684 J 2.495 2.505 K 0.257 0.262 DT8683 L 0.312 0.317 DT8686 M 0.235 0.240 N 0.100 0.140 O 0.540 0.560 P 0.490 0.510 Q 3.609 3.619 R 2.470 2.510 S 0.240 0.270 T 0.100 0.180 U 0.313 0.318 DT8686 X Y 1.125 1.145 W 1.565 1.585 X Y Z AA AB AB AC AD AE AF	124	- <i>12</i> 2	-122		
E 1.245 1.255	- 118	.118	.118		
F 1.245 1.255	.219	:220 7.249	-219		/B.//
F 1.245 1.255		1,249	1.250		
G 5.990 6.010 H 0.510 0.515 D -5/5 I 1.674 1.684 J 2.495 2.505 K 0.257 0.262 DT8683 L 0.312 0.317 DT8686 M 0.235 0.240 N 0.100 0.140 O 0.540 0.560 P 0.490 0.510 Q 3.609 3.619 R 2.470 2.510 S 0.240 0.270 T 0.100 0.180 U 0.313 0.318 DT8686 V 1.125 1.145 W 1.565 1.585 X Y Z AA AB AC AD AE AF		17.250	1-249		
H 0.510 0.515 I 1.674 1.684 J 2.495 2.505 K 0.257 0.262 DT8683 L 0.312 0.317 DT8686 M 0.235 0.240 N 0.100 0.140 O 0.540 0.560 P 0.490 0.510 Q 3.609 3.619 R 2.470 2.510 S 0.240 0.270 T 0.100 0.180 U 0.313 0.318 DT8686 V 1.125 1.145 W 1.565 1.585 X Y Z AA AB AC AB AC AD AE AF	5.991	5.997	6.996		
1	0.515	0.575	0.575		
K 0.257 0.262 DT8683 L 0.312 0.317 DT8686 M 0.235 0.240 □ 23 N 0.100 0.140 □ 123 O 0.540 0.560 □ 548 P 0.490 0.510 □ 502 Q 3.609 3.619 □ 3.603 R 2.470 2.510 □ 2.503 S 0.240 0.270 □ 253 T 0.100 0.180 □ 145 U 0.313 0.318 DT8686 ####################################	7.649	1.649	1.679		
K 0.257 0.262 DT8683 L 0.312 0.317 DT8686 M 0.235 0.240 □ 23 N 0.100 0.140 □ 123 O 0.540 0.560 □ 548 P 0.490 0.510 □ 502 Q 3.609 3.619 □ 3.603 R 2.470 2.510 □ 2.503 S 0.240 0.270 □ 253 T 0.100 0.180 □ 145 U 0.313 0.318 DT8686 ####################################	2499	2.500	2.499		
M 0.235 0.240		7			
N 0.100 0.140			,/		
N 0.100 0.140	8.237	0.236	0.236		
O 0.540 0.560 P 0.490 0.510 Q 3.609 3.619 R 2.470 2.510 S 0.240 0.270 T 0.100 0.180 U 0.313 0.318 DT8686 V 1.125 1.145 W 1.565 1.585 X Y Z AA AB AC AD AE AF	./23	. 121	-/21		
P 0.490 0.510	.550	.548	. 550		
Q 3.609 3.619 3.619 R 2.470 2.510 Q.500 S 0.240 0.270 T 0.100 0.180 U 0.313 0.318 DT8686 V 1.125 1.145 W 1.565 1.585 X Y Z AA AB AC AD AE AF	-201	.500	-499		
R 2.470 2.510	3.6/4	3.614	3614		
S 0.240 0.270 T 0.100 0.180 U 0.313 0.318 DT8686 V 1.125 1.145 W 1.565 1.585 X Y Z AA AB AC AD AE AF	2.500	ã.500 .252	2.500		
T 0.100 0.180 . 145 U 0.313 0.318 DT8686 . 38 V 1.125 1.145	251	.252	.253		
U 0.313 0.318 DT8686	-145	-145	-145		
V 1.125 1.145 /-/38 W 1.565 1.585 /.577 X Y Z AA AB AC AD AE AF			-/		
W 1.565 1.585 /. 577 X Y Z AA AB AC AD AE AF	1.135	1.135	1.734		
Y Z	1.570	1.574	1.573		
Z					
AA					
AA					
AB AC AD AE AF					
AC AD AE AF					
AD AE AF					
AE AF					
AF					
AH					

Measured by:	J.L	1Er .	Audited by づ. G
Date:	06/06/26	06/07/24	Date: 06/07/26

Rev	Date	Change	Revised by	Approved
Α		New Issue	ЯF	
В	99.04.19	Incorporated DSI 9095, DSI 9102 & DSI 9122 Rev. A	RF	
С	99.11.10	Added Dim. R-T	RF	
D	02.12.12	Reformat; Added Dim. U-W & DT8683, DT8686	KJ/RF	#

DART AEROSPACE LTD	Work Order:	27671
	Y	
Description: 206 Saddle, Outboard, Right side	Part Number:	D2665-2
Inspection Dwg: D2665 Rev. B		Page 1 of 1


Inspect dimensions highlighted on inspection sheet drawing D2665 Rev. B and record below:

				Recorded Actual Dimensions					
Dim	Min	Max	Go/No Go Gauge	1	2	3	4	Ву	Date
Α	0.100	0.140		./23	5128	,122	.120		
В	0.100	0.140		./24	-126	.126	.122		
С	0.100	0.140		-119	0121	.119	୍//ବ		
D	0.210	0.230		.220	.220	-220	226		
E	1.245	1.255		1.250	1250	1,250	1,250		
F	1.245	1.255		1.249	1,249	1.249	1,249		
G	5.990	6.010		5-995	5.997	5.997	5518		
Н	0.510	0.515		0.275	6-515	0.515	212-0		
ı	1.674	1.684		1.679	1679	1.674	1,675		
J	2.495	2.505		2,498	2/498	2,498	2 498		
K	0.257	0.262	DT8683				1		
L	0.312	0.317	DT8686			/		٠	
M	0.235	0.240		0.236	0.237	6.237	0.235		
N	0.100	0.140		-118	-120	.119	-/20		
0	0.540	0.560		.550	1549	-549	.549		
Р	0.490	0.510		102.	249	4925	497		
Q	3.609	3.619	-	376/4	3.613	3,6/3	.3.613	ľ	
R	2.470	2.510		2500	2.500	2,500	2.200		
S	0.240	0.270		-253	£258	259	. 256		
Т	0.100	0.180		-145	-145	-145	145		
U	0.313	0.318	DT8686				7		
V	1.125	1.145		7.731	7./32	1.131	11345		
W	1.565	1.585		1.570	1.570	1.570	1574		
X			7						
Y	-		,						
Z									
AA									
AB									
AC						4			
AD									
AE									
AF									
AG		-		· ·					
AH							-		
	Acc	ept/Reje	ct	4	Francis p	lad			

		[\[\langle \]
Measured by: J.L /	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	Audited by 🕳 5.6
Date: 0/0/0/20 /	06.06.27	Date: 06/07/36

Rev	Date	Change	Revised by	Approved
A		New Issue	RF	
В	99.04.19	Incorporated DSI 9095, DSI 9102 & DSI 9122 Rev. A	RF	
С	99.11.10	Added Dim. R-T	RF	
D	02.12.12	Reformat; Added Dim. U-W & DT8683, DT8686	KJ/RF	#

			·
			,
•	*		
i .			
	一方分手に入り		
	· · · · · · · · · · · · · · · · · · ·	`	
		4	
			· ·
,			



Copyright 1997 by DART AEROSPACE USA, INC

WITHOUT NOTICE
WORK ORDER
NO. 27671